


Our BETA 60 high density ultra flex delivers precise, even, fully controllable illumination from a super flexible lightweight strip. Supplied ready to use, BETA 60 is the perfect interior/ exterior LED design solution.



BETA 60 SMD 5050

The LED Creative BETA 60 range is a premium quality LED flex, manufactured to the highest standards using premium silicone and advanced, robust components.

Supplied in 5m rolls, pre-assembled and calibrated ready for use, BETA 60 is super flexible, highly controllable and available in a selection of colour temperatures and IP ratings, including splashproof and waterproof options to allow maximum versatility across a wide variety of applications.

Perfect for creative media and broadcast entertainment installations, set building or architectural applications, BETA 60 is ideal for highlighting or accentuation of design elements, edging set pieces or for delivering intense, even lightbox illumination.

Cool running and drawing only 14.4W per metre, BETA 60 is the ultimate low energy LED flex solution - flexible, adaptable and simple to use.



LED CREATIVE LIMITED

Unit 5 Executive Park, Hatfield Road, St Albans, Hertfordshire AL1 4TA United Kingdom
+44 (0) 1727 569387

info@led-creative.co.uk
led-creative.co.uk

BETA 60 SMD 5050

Features

Flexible, low energy RGB LED light source.

Virtually infinite colour rendering capabilities.

Ideal for use where multiple light sources are required within the same illumination space.

IP rated standard, splashproof and waterproof versions available - ideal for use outdoors or in harsh environments.

Controllable via lighting console (DMX) or manual dimmer.

Perfect for lightboxes, void and edge lighting.

Low maintenance.

Product Range

BETA 60 RGB



BETA 2600K Warm White



BETA 5600K Neutral White



BETA 6500K Cool White



24V ALPHA 60 range also available


please refer to separate Technical Data Sheet for details

Technical

| | | | |
|-----------------------|----------------------|------------------------|---------------|
| LEDs per metre | 60 | Power use per metre | 0.014kWh |
| Watts per metre | 14.4W | Standard length | 5 metres |
| Voltage | 12V DC | Minimum cut point | 100mm |
| PCB colours available | White, Black | Cut and Tail Service | Yes |
| Light Output | 720 Lumens per metre | Operating Temp | -40°C - +50°C |
| Beam angle | 120° | Colour Rendering Index | >70 |

Dimensions*

| *Size variable depending on IP rating | | |
|---------------------------------------|-------|--------|
| IP RATING | DEPTH | WIDTH |
| IP20 | 2.5mm | 10mm |
| IP65 | 4mm | 11mm |
| IP68 | 5mm | 12.5mm |
| Standard length: 5000mm | | |



Standard length: 5000mm

Width and depth variable depending on IP rating (please refer to chart above)



LED CREATIVE LIMITED

Unit 5 Executive Park, Hatfield Road, St Albans, Hertfordshire AL1 4TA United Kingdom
+44 (0) 1727 569387

info@led-creative.co.uk
led-creative.co.uk