
LED GREATIVE

Our DELTA range of super slim flex delivers bright, precise RGB and white illumination from an ultra slim ribbon. Compact and discreet DELTA LED ribbon and is a powerful, controllable solution for adding clean, bright accents to edging and set pieces where illumination space is limited.



DELTA LED RIBBON

LED Creative DELTA LED packs 60 LEDs into every metre of illumination to deliver sharp, intense quality in light from a single run of slimline ribbon.

Bright, flexible and highly controllable, the LEDs used in our DELTA system are switchable between RGB and White making it versatile enough to deal with almost any application, particularly where available space is limited or for more intricate installations.

Available in a selection of colour temperatures and IP ratings, including splashproof and waterproof options DELTA LED provides versatility across a wide variety of applications. Fully controllable, both manually or via DMX, DELTA LED is also totally compatible with LED BIT Control systems for precise management over every LED.

Cool running and drawing only 20W per metre, DELTA LED is simply one of the brightest slimline low energy LED flex solutions available.





DELTA LED RIBBON

Features

Flexible, low energy, slimline LED light source.

Full RGB and Colour temperature accuracy from each individual LED

High density, 60 LEDs per metre.

IP rated standard, splashproof and waterproof versions available - ideal for use outdoors or in harsh environments.

Controllable via lighting console (DMX), manual dimmer or LED Creative BIT Control systems.

Perfect for bright, intense highlights, light boxes or edge lighting.

Low maintenance.

Product Range

DELTA 2900K RGB & Warm White













DELTA 6500K

RGB & Cool White













DELTA 2600K & 6000K

RGB & Warm White & Cool White













Technical

| LEDs per metre | 60 | Power use per metre | 0.020kWh |
|-----------------------|-----------------------|------------------------|---------------|
| Watts per metre | 20W | Standard length | 5 metres |
| Voltage | 24V DC | Minimum cut point | 100mm |
| PCB colours available | White | Cut and Tail Service | Yes |
| Light Output | 1150 Lumens per metre | Operating Temp | -40°C - +50°C |
| Beam angle | 120° | Colour Rendering Index | 80+ |



Standard length: 5000mm

Width and depth variable depending on IP rating (please refer to chart above)



